



REV.	Description	Date
6	arrangement , rate voltage revise	2014/6/13
7	rate voltage, contact resistance, insertion/withdrawal force revise	2016/4/19
8	rated current revise	2018/10/5
9	arrangement revise	2020/11/23

Specification of connector

General Characteristics

- Locking system : screw M24
- Shell protection : IP67
- Rated voltage : 360V, 60V(9BP)
- Rated current : Large pin 35A
: Small pin 10A
- Contact resistance : Large pin <5mΩ
: Small pin <30mΩ
- Insertion force : <80N
- Withdrawal force : <80N

Materials

- Pin contact : brass
- Contact plating : gold
- Male insert : PA
- Ring nut : PA

Specification of cable

Material Jacket	PVC	PUR

RoHS

CONTACT ARRANGEMENT FRONT VIEW (MALE)	2AP	8P	9P	10P	3BP	7BP	9AP	9BP


Unicable Co., Ltd. 國陽電業有限公司
 5F., No. 111-33, Sec. 4, San Ho Road., San Chung Dist., New Taipei City, Taiwan
<http://www.unicable.com.tw> Tel:+886-2-2286-2122 Fax:+886-2-2286-1010

DATE	2020/11/23	PART NO.	UT-D258M4-XP
DWN	GINA	REV.	9
CHK			
ITEM	High Power M24	UNIT	MM