

Part No. : UT-5270-XP-X


pin no.

1-cable OD : 7.5-8.5mm
 2-cable OD : 8.6-9.5mm
 3-cable OD : 9.6-10.5mm
 4-cable OD : 10.6-11.5mm


REV.	Description	Date

Specification of connector

Locking system : Quick Push Lock
 Termination : solder
 Shell protection : IP68
 Contact resistance : <10mΩ
 Insulation resistance : >10MΩ



Cable preparation



RoHS
 TOLERANCE ±0.5

5	Nut	PA
4	Seal	TPR
3	Body	PA
2	Terminal	Brass/Gold plated
1	Female insert	PA
Item	Description	Material&Plating

CONTACT ARRANGEMENT FRONT VIEW (FEMALE)	2P		3P		4P		5P		6P	
Rated voltage	300V		250V		60V					
Rated current	20A		10A		10A					



Unicable Co., Ltd. 國陽電業有限公司

5F., No. 111-33, Sec. 4, San Ho Road., San Chung Dist., New Taipei City, Taiwan
<http://www.unicable.com.tw> Tel:+886-2-2286-2122 Fax:+886-2-2286-1010

DATE	2020/9/25	PART NO.	UT-5270-XP-X
DWN	GINA	REV.	0
CHK			
UNIT	MM		

ITEM	Type J(J3): female conn. 2-6P
------	-------------------------------